

Performance Data

Motor Type	Type	Rating (50 HZ, 2870RPM)				In	Locked rotor	Eff.	Pf.	C		Thrust Load
		HP	KW	V	PH	A	A	%	%	uf	Starting Capacitor	N
4PD	4PD0.37	1/2	0.37	220	1	2.7	7.3	63	98	18	/	3000
	4PD0.55	3/4	0.55	220		3.8	11.2	68	98	25	/	
	4PD0.75	1	0.75	220		5.1	16.3	68	99	25	/	
	4PD1.1	1 1/2	1.1	220		7.1	21.2	70	99	35	/	
	4PD1.5	2	1.5	220		9.6	32.5	72	98	45	/	
4P	4P0.37	1/2	0.37	380	3	1.0	3.7	65	80	/	/	
	4P0.55	3/4	0.55	380		1.5	6.4	70	77	/	/	
	4P0.75	1	0.75	380		1.9	8.6	71	80	/	/	
	4P1.1	1 1/2	1.1	380		2.7	13.6	74	79	/	/	
	4P1.5	2	1.5	380		3.8	18.9	74	78	/	/	
	4P2.2	3	2.2	380		5.2	26.3	76	81	/	/	
	4P0.37	1/2	0.37	220		1.8	6.4	65	80	/	/	
	4P0.55	3/4	0.55	220		2.5	11.0	70	77	/	/	
	4P0.75	1	0.75	220		3.3	14.9	71	80	/	/	
	4P1.1	1 1/2	1.1	220		4.7	23.6	74	79	/	/	
	4P1.5	2	1.5	220		6.6	32.7	74	78	/	/	
	4P2.2	3	2.2	220		9.0	45.5	76	81	/	/	
4PDS	4PDS0.75	1	0.75	220	1	5.5	30.4	67	94	25	150uf/330VAC	
	4PDS1.1	1 1/2	1.1	220		7.8	37.5	68	95	35	200uf/330VAC	
	4PDS1.5	2	1.5	220		10.5	52.7	70	94	40	250uf/330VAC	